

Reliable plug-and-play 44-inch small team printer





Easily do more in less time and grow your

- Get the job done quickly without sacrificing quality thanks to this printer's fast (Economode) print setting—2 A1/D-sized prints per minute.
- Improve your media loading with a convenient, hassle-free front-loading top roll printer, and save time with alerts that facilitate timely replacement.
- Small teams can share this printer thanks to its built-in network card.
- Increase your possibilities with system enhancements like more memory and optional PostScript accessory.(1
- Print batch HP-GL/2, DWF, PDF, JPEG, TIFF, and MS Office 2007 (Word, Excel, PowerPoint, Outlook) files easily—without opening any application—thanks to the free HP Instant Printing Utility.



- Achieve rich, dark blacks and fine detailed lines with HP Vivera inks, including 2 HP Vivera blacks and a gray ink in this 6-ink printing system.
- Produce exacting detail with 0.02 mm (0.0008 in) minimum line width, (2 and highly accurate drawings with 0.1% line accuracy.
- Easily create stunning large-format posters that convey your message loud and clear with the optional Serif PosterDesigner Pro for HP.(3)
- Transform your everyday printing with 2 HP media innovations—new and improved HP

bond papers with ColorPRO Technology and HP Recycled Bond Paper, made of 100% recycled base paper.

Optimize blueprints—use this printer's new printing mode for generic natural tracing paper.

Focus on your design with a reliable printer

- Work with confidence knowing this printer can easily process complex files.
- Increase your memory capabilities with a 160 GB hard disk version printer, including 8 GB of dedicated memory for fast file processing.(4
- Experience greater operating system support with original HP-GL/2 and RTL.
- Experience efficient, reliable printing with Original HP printing supplies and printing materials.
- Manage your printer fleet and costs with HP Web Jetadmin and the HP accounting tool.



HP DES**i**Gnjet t770 pr**i**nter

- Save paper with blank print area detection, image auto-rotate and realistic
- print previews

 Less ink wasted thanks to efficient installation and maintenance routines

 Free, convenient cartridge and printhead recycling¹¹

 Supports 100% recycled HP media

 ENERGY STAR® Qualified Product



















- The PostScript accessory is an optional accessory to be purchased separately (includes 6 GB memory upgrade).
- HP-GL/2 addressable
- Serif PosterDesigner Pro for HP is an optional software accessory to be purchased separately.
- The HP Designjet T770 44-in Printer includes 2 GB of standard memory and an optional 6 GB memory accessory, which must be purchased separately

HP DESIGNJET T770 PRINTER SERIES

Print Speed(1	
Line drawings ⁽²	Fast: 28 sec/page on A1/D, 103 A1/D prints per hour
Color images	Fast: 51 m²/hr (549 ft²/hr)/²
Printing	Best: 3.1 m ² /hr (33.3 ft ² /hr) ⁽³
Print resolution	Up to 2400 x 1200 optimized dpi
Margins	Roll: 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in)
(top x bottom x left x right) Technology	Sheet: 5 x 16.75 x 5 x 5 mm (0.2 x 0.67 x 0.2 x 0.2 in) HP Thermal Inkjet
Ink types	Dye-based (C, M, Y, G, PK); pigment-based (MK)
Ink colors	Cyan, gray, magenta, matte black, photo black, yellow
Ink drop	6 pl (C, M, PK, G), 9 pl (Y, MK)
Ink cartridge size	130 ml (cyan, gray, magenta, matte black, photo black, yellow)
Printheads	69 ml (cyan, gray, magenta, photo black, yellow) 3 (matte black and yellow, magenta and cyan, gray and photo black)
Line accuracy	+/- 0.1% ⁽⁴
Minimum line width	0.02 mm (0.0008 in) (HP-GL/2 addressable)
Guaranteed minimum line width	0.06 mm (0.0024 in) (ISO/IEC 13660:2001(E)) ^{[5}
Maximum print length Media	91 m (300 ft) (OS and application dependent)
Handling	Sheet feed; roll feed; automatic cutter
Types	Bond and coated papers, technical papers, films, photographic papers,
Weight	backlit materials, self-adhesive materials 60 to 328 g/m²
Size	210 x 279 to 1118 x 1676 mm (8.26 x 11 to 44 x 66 in) sheets;
mt . I	27.94 to 111.76 cm (11 to 44 in) rolls
Thickness	Up to 0.8 mm (31.5 mil)
Memory	Base Model: 2 GB dedicated file-processing memory ¹⁶
	Hard Disk Version Printer: 8 GB dedicated file-processing memory, 160
Connectivity	GB hard disk ¹⁶
Connectivity Interfaces (standard)	1 Fast Ethernet (100Base-T) port, 1 Hi-Speed USB 2.0 certified port, 1
, ,	EIO Jetdirect accessory slot
Interfaces (optional)	HP Jetdirect EIO print servers
Print languages (standard)	Base model: HP-GL/2, HP-RTL, HP PCL 3 GUI Hard Disk Version Printer: HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI
Print languages (optional)	Adobe® PostScript® 3™, Adobe PDF 1.7 (with optional PostScript
D: (:	Upgrade accessory)
Drivers (included)	HP-GL/2, HP-RTL drivers for Windows® (optimized for AutoCAD 2000 and higher); HP PCL 3 GUI driver for Mac OS X; support for Citrix XenApp and
	Citrix XenServer environments; PostScript Windows, Linux, and Mac drivers
Recommended system requires	with optional dongle (will remove HP PCL 3 GUI driver support)
Mac	Mac OS X v 10.4, Mac OS X v 10.5: PowerPC G4, G5, or Intel Core
	Processor; 1 GB RAM; 2 GB available hard disk space
Windows	Windows XP® (SP2 or later): Intel® Pentium® family or AMD® K6/Athlon/ Duron family (1 GHz), 1 GB RAM, 2 GB available hard disk space;
	Windows Vista®: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB
Dimensions (w x d x h)	RAM, 2 GB available hard disk space
Printer	1770 x 702 x 1050 mm (69.7 x 27.6 x 41.3 in)
Shipping	
	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)
Weight	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)
Weight Printer	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb)
Weight Printer Shipping	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in)
Weight Printer	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges,
Weight Printer Shipping	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif
Weight Printer Shipping	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges,
Weight Printer Shipping What's in the box Environmental ranges Operating temperature	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F)
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord
Weight Printer Shipping What's in the box Environmental ranges Operating temperature	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type)
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F)
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F)
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type)
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A)
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A)
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound power, active Sound power, standby	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A)
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A)
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound power, active Sound power, standby Power consumption Maximum Powersave	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A)
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Storage humidity Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, standby Power consumption Maximum Powersave Off	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (<25 watts with embedded DFE) 0.1 watts
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound power, active Sound power, standby Power consumption Maximum Powersave	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A)
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 46 dB(A) 46 dB(A) 47 wotts 48 dB(A) 48 dB(A) 49 dB(A) 40 dB(A) 40 dB(A) 40 dB(A) 40 dB(A) 40 dB(A) 41 dB(A) 42 dB(A) 43 dB(A) 44 dB(A) 44 dB(A) 45 dB(A) 44 dB(A) 45 dB(A) 46 dB(A) 47 wotts 48 dB(A) 49 dB(A) 40 dB(
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant);
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 46 dB(A) 46 dB(A) 47 wotts 48 dB(A) 48 dB(A) 49 dB(A) 40 dB(A) 40 dB(A) 40 dB(A) 40 dB(A) 40 dB(A) 41 dB(A) 42 dB(A) 43 dB(A) 44 dB(A) 44 dB(A) 45 dB(A) 44 dB(A) 45 dB(A) 46 dB(A) 47 wotts 48 dB(A) 49 dB(A) 40 dB(
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Recommended operating temperature Recommended operating temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules),
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating temperature Recommended operating humidity Storage humidity Storage humidity Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification Safety	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (IVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, active Sound power, active Sound power, active Sound power, active Off Power consumption Maximum Powersave Off Power requirements Certification Safety Electromagnetic	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, standby Sound power, active Sound power, standby Power consumption Maximum Powersave Off Power requirements Certification Safety Electromagnetic	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia (GOS1); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) WEEE, EU RoHS, China RoHS, REACH, Eup, FEMP
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Acoustic Sound pressure, active Sound pressure, active Sound power, active Sound power, active Sound power, active Off Power consumption Maximum Powersave Off Power requirements Certification Safety Electromagnetic	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia (GOST); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea
Weight Printer Shipping What's in the box Environmental ranges Operating temperature Recommended operating temperature Storage temperature Recommended operating humidity Storage humidity Storage humidity Storage humidity Sound pressure, active Sound pressure, active Sound pressure, active Sound power, active Sound power, active Sound power requirements Certification Safety Electromagnetic Environmental ENERGY STAR® qualified	1930 x 766 x 778 mm (75.98 x 30.16 x 30.7 in) 81.6 kg (180 lb) 111 kg (244 lb) Printer, printheads (3 x 2 colors each), introductory ink cartridges, 44-in stand, 44-in spindle, Quick Reference Guide, setup poster, Serif PosterDesigner Pro for HP poster, start-up software, power cord 5 to 40° C (41 to 104° F) 15 to 35° C (59 to 95° F) (depending on paper type) -25 to 55° C (-13 to 131° F) 20 to 80% RH (depending on paper type) 0 to 95% RH 46 dB(A) 26 dB(A) 6.2 B(A) 4.4 B(A) 120 watts < 7 watts (< 25 watts with embedded DFE) 0.1 watts Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max USA and Canada (CSA certified); EU (LVD and EN60950-1 compliant); Russia (GOS1); Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE) Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) WEEE, EU RoHS, China RoHS, REACH, EuP, FEMP

FOR MORE INFORMATION, VISIT OUR WEBSITE AT WWW.HP.COM/GO/DESIGNJETT770

Postignier 1770 44-in Printer	ORDERING INFORMATION		
Name	Product		
Accessories	CH539A		
CASTONA		HP Designjet T770 44-in Hard Disk Version Printer	
New York Programmer Degrade		HP Designat 44-inch Poll Food Spindle	
P. Postigriet 1770 Memory Upgrade			
Cy389A			
Original HP printheods C938DA HP 72 Gray and Photo Black Printheod C938AA HP 72 Margenta and Cyan Printheod C938AA HP 72 Margenta and Cyan Printheod C939AA HP 72 69ml Rode and Vallow Printheod C9397A HP 72 69ml Cyan Ink Cortridge C9399A HP 72 69ml Cyan Ink Cortridge C9400A HP 72 69ml Cyan Ink Cortridge C9401A HP 72 130ml Morte Black Ink Cortridge C9401A HP 72 130ml Morte Black Ink Cortridge C9401A HP 72 130ml Morte Black Ink Cortridge C937AA HP 72 130ml Mogenta Ink Cortridge C937AB HP 80ml Mogenta Ink Cortridge C938AB HP 72 130ml Mogenta Ink Cortridge			
C938AA			
C938AA			
C938AA			
C9397A HP 72 69m (Sport Ink Cortridge C9399A HP 72 69m (Sport) Ink Cortridge C9400A HP 72 69m (Sport) Ink Cortridge C9401A HP 72 69m (Sport) Ink Cortridge C9401A HP 72 130m (Manta Black Ink Cortridge C9401A HP 72 130m (Park Block Ink Cortridge C937A HP 72 130m (Sport Ink Cortridge C60		HP 72 Matte Black and Yellow Printhead	
G9399A			
C9399A			
C9400A			
G9370A	C9400A		
G9370A			
G9371A			
(29372A HP 72 130·ml Magenta Ink Cartridge (29373A HP 72 130·ml Yellow Ink Cartridge (29374A HP 72 130·ml Gray Ink Cartridge (29374A HP Super Heavyweight Plus Matte Paper 210 g/m², 36 in. x 100 ft/1067 mm x 30,5 m (26627A HP Super Heavyweight Plus Matte Paper 210 g/m², 36 in. x 100 ft/1067 mm x 30,5 m (26364A HP Super Heavyweight Coated Paper 130 g/m², 36 in. x 100 ft/1067 mm x 30,5 m (26369C HP Heavyweight Coated Paper 130 g/m², 32 in. x 100 ft/1067 mm x 30,5 m (26369C HP Heavyweight Coated Paper 130 g/m², 34 in. x 150 ft/610 mm x 45,7 m (NA & EMEA only) (26019B HP Coated Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (NA & EMEA only) (26019B HP Coated Paper 90 g/m², 36 in. x 150 ft/914 mm x 91,4 m (26040A HP Coated Paper 90 g/m², 36 in. x 150 ft/914 mm x 91,4 m (26040A HP Gray 10 g/m², 36 in. x 150 ft/914 mm x 45,7 m (NA & LAR only) (26036A HP Gray 10 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) (26036A HP Gray 10 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) (26036A HP Gray 10 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) (26036A HP Gray 10 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) (26036A HP gray 10 g/m²) (26036A			
Original HP printing materials			
Original HP printing materials			
Ocidinary HP Super Heoryweighl Plus Mottle Paper 210 g/m², 3d in. x 100 ft/104 mm x 30,5 m C663BA HP Super Heoryweighl Plus Mottle Paper 130 g/m², 42 in. x 100 ft/1047 mm x 30,5 m C6030C HP Heoryweighl Coated Paper 130 g/m², 3c in. x 100 ft/1047 mm x 30,5 m C6569C HP Heoryweighl Coated Paper 130 g/m², 4c in. x 100 ft/1047 mm x 30,5 m C659B HP Heoryweighl Coated Paper 130 g/m², 2d in. x 150 ft/610 mm x 45,7 m C6010B HP Coated Paper 90 g/m², 3d in. x 150 ft/610 mm x 45,7 m C6900A HP Coated Paper 90 g/m², 3d in. x 150 ft/914 mm x 45,7 m C6930A HP Cated Paper 90 g/m², 3d in. x 150 ft/610 mm x 45,7 m (NA & LAR only) now with ColorPRO Technology C6930A HP Bright White Inkjel Paper 90 g/m², 24 in. x 150 ft/610 mm x 45,7 m (NA & LAR only) now with ColorPRO Technology C6030A HP Bright White Inkjel Paper 90 g/m², 24 in. x 150 ft/610 mm x 45,7 m (NA & LAR only) now with ColorPRO Technology C630A HP Bright White Inkjel Paper 90 g/m², 3d in. x 150 ft/914 mm x 45,7 m (NA & LAR only) now with ColorPRO Technology C630A HP Bright White Inkjel Paper 90 g/m², 3d in. x 150 ft/914 mm x 45,7 m (NA & LAR only) now with ColorPRO Technology C630A HP Bright White Inkjel Paper 90 g/m², 3d in. x 150 ft/914 mm x 45,7 m C640A HP Bright White Inkjel Paper 90 g/m², 3d in. x 150 ft/914 mm x 45,			
Ge628A			
C6030C			
G0196 A HP Coated Paper 90 g/m², 24 in. x 150 ft/610 mm x 45,7 m (NA & EMEA only) C60108 HP Coated Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (NA & EMEA only) C6980A HP Coated Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (NA & LAR only) now with ColorPRO Technology (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (NA & LAR only) now with ColorPRO Technology (National Paper 90 g/m², 24 in. x 150 ft/910 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology (National Paper 90 g/m², 24 in. x 150 ft/910 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology (National Paper 90 g/m², 24 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,7 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,7 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,5 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,5 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,5 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,5 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,5 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,5 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,5 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,5 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,5 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,5 m (National Paper 90 g/m², 36 in. x 150 ft/914 mm x	C6030C	HP Heavyweight Coated Paper 130 g/m², 36 in. x 100 ft/914 mm x 30,5 m	
C6019B			
C6020B			
C6980A HP Coated Paper 90 g/m², 36 in. x 300 ft/914 mm x 91,4 m HP Bright White Inkjet Paper 90 g/m², 24 in. x 150 ft/610 mm x 45,7 m (NA & LAR only) now with ColorPRO Technology C6035A HP Bright White Inkjet Paper 90 g/m², 24 in. x 150 ft/610 mm x 45,7 m (NA & LAR only) now with ColorPRO Technology C1861A HP Bright White Inkjet Paper 90 g/m², 24 in. x 150 ft/914 mm x 45,7 m (NA & LAR only) now with ColorPRO Technology C6036A HP Bright White Inkjet Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology C6036A HP Bright White Inkjet Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology G1445A HP Bright White Inkjet Paper 90 g/m², 36 in. x 300 ft/914 mm x 91,4 m now with ColorPRO Technology G145A HP Bright White Inkjet Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & JP only) now with ColorPRO Technology G1397A HP Universal Bond Paper 80 g/m², 36 in. x 150 ft/914 mm x 45,7 m now with ColorPRO Technology G1397A HP Natural Tracing Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m now with ColorPRO Technology G1421A HP Matter Introduce Technology G1421A HP Matter Introduce Technology G1421A HP Matter Introduce Technology G1421A HP Universal High-gloss Photo Paper 190 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) G1421A HP Universal Semigloss Photo Paper 190 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) G1421A HP Premium Matte Photo Paper 210 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) G26450A HP Premium Matte Photo Paper 210 g/m², 36 in. x 100 ft/914 mm x 22,9 m (NA, EMEA, AP only) G8834A HP Cockle-free Heavyweight Coated Paper 170 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) G8834A HP Cockle-free Heavyweight Coated Paper 170 g/m², 36 in. x 100 ft/914 mm x 30,5 m (US & EMEA only) G888A HP Cockle-free Heavyweight Coated Paper 170 g/m², 42 in. x 100 ft/914 mm x 30,5 m (US & EMEA only) G883A HP Cockle-free Coated Paper 100 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA			
C6035A HP Bright White Inkjet Poper 90 g/m², 24 in. x 150 ft/610 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology C1861A HP Bright White Inkjet Poper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (NA & LAR only) now with ColorPRO Technology C6036A HP Bright White Inkjet Poper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology C6810A HP Bright White Inkjet Poper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) now with ColorPRO Technology Q1445A HP Bright White Inkjet Poper 90 g/m², 36 in. x 300 ft/914 mm x 91,4 m now with ColorPRO Technology Q145A HP Bright White Inkjet Poper 90 g/m², (A1) 23.39 in. x 150 ft/954 mm x 45,7 m (EMEA & JP only) now with ColorPRO Technology Q1397A HP Universal Bond Poper 80 g/m², 36 in. x 150 ft/914 mm x 45,7 m now with ColorPRO Technology Q1397A HP Notural Tracing Poper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m now with ColorPRO Technology Q1421A HP Universal High gloss Photo Poper 190 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) Q1421A HP Universal Semi-gloss Photo Poper 190 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) Q4421A HP Puniversal Semi-gloss Photo Poper 210 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) Q5459A HP Premium Matte Photo Poper 210 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) Q6459A HP Premium Matte Photo Poper 210 g/m², 36 in. x 75 ft/914 mm x 22,9 m (NA, EMEA, AP only) Q7660A HP Reverse Print Matte Backlit Film 160 g/m², 36 in. x 75 ft/914 mm x 22,9 m (NA, EMEA, AP only) Q7660A HP Reverse Print Matte Backlit Film 160 g/m², 36 in. x 75 ft/914 mm x 22,9 m (US & EMEA only) Q7688A HP Cockle-free Heavyweight Coated Poper 170 g/m², 36 in. x 75 ft/914 mm x 30,5 m (US & EMEA only) Q7688A HP Cockle-free Heavyweight Coated Poper 170 g/m², 36 in. x 100 ft/1067 mm x 30,5 m (US & EMEA only) Q7688A HP Cockle-free Heavyweight Coated Poper 170 g/m², 42 in. x 150 ft/914 mm x 45,7 m (US & EMEA only) Q7688A HP Cockle-free Coated Poper 100 g/m², 36 in. x 150 ft/914			
C6035A HP Bright White Inkjet Paper 90 g/m², 24 in. x 150 ft/610 mm x 45,7 m (EMEA & AP only) now with Color®RO Technology C1861A HP Bright White Inkjet Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (NA & LAR only) now with Color®RO Technology C6036A HP Bright White Inkjet Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) now with Color®RO Technology C6810A HP Bright White Inkjet Paper 90 g/m², 36 in. x 150 ft/914 mm x 91,4 m now with Color®RO Technology Q1445A HP Bright White Inkjet Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP only) now with Color®RO Technology Q1397A HP Universal Bond Paper 80 g/m², 36 in. x 150 ft/914 mm x 45,7 m now with Color®RO Technology C3868A HP Natural Tracing Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m now with Color®RO Technology C3868A HP Natural Tracing Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m now with Color®RO Technology C3868A HP Natural Tracing Paper 90 g/m², 36 in. x 150 ft/914 mm x 30,5 m HP (Lear Film 174 g/m², 36 in. x 75 ft/914 mm x 22,9 m G1427A HP Universal High-gloss Photo Paper 190 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) Q1421A HP Universal High-gloss Photo Paper 190 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) G26450A HP Premium Matte Photo Paper 210 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) G8834A HP Selfadhesive Gloss Polyropylene 120 g/m², 36 in. x 75 ft/914 mm x 22,9 m (NA, EMEA, AP only) G8834A HP Selfadhesive Gloss Polyropylene 120 g/m², 36 in. x 100 ft/914 mm x 22,9 m (US & EMEA only) G883A HP Cockle-free Heavyweight Coated Paper 170 g/m², 36 in. x 100 ft/914 mm x 30,5 m (US & EMEA only) G883A HP Cockle-free Heavyweight Coated Paper 170 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only) G883A HP Cockle-free Heavyweight Coated Paper 170 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only) G883A HP Cockle-free Coated Paper 100 g/m², 34 in. x 150 ft/914 mm x 45,7 m (US & EMEA only) G883A HP Cockle-free Coated Paper 100 g/m², 36 in. x 150 ft/914 mm x 45,7 m (C1860A		
C1861A	C6035A	HP Bright White Inkjet Paper 90 g/m², 24 in. x 150 ft/610 mm x 45,7 m (EMEA & AP only)	
C636A	C1861A	HP Bright White Inkjet Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (NA & LAR only)	
C6810A	C6036A	HP Bright White Inkjet Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m (EMEA & AP	
Q1445A	C6810A	HP Bright White Inkjet Paper 90 g/m², 36 in. x 300 ft/914 mm x 91,4 m	
C3868A HP Natural Tracing Paper 90 g/m², 36 in. x 150 ft/914 mm x 45,7 m C3875A HP Clear Film 174 g/m², 36 in. x 150 ft/914 mm x 22,9 m 51642B HP Matte Film 160 g/m², 36 in. x 125 ft/914 mm x 22,9 m 51642B HP Matte Film 160 g/m², 36 in. x 125 ft/914 mm x 38,1 m C1427A HP Universal High-gloss Photo Paper 190 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) Q1421A HP Universal Semigloss Photo Paper 190 g/m², 36 in. x 100 ft/914 mm x 30,5 m (NA, EMEA, AP only) CG459A HP Premium Matte Photo Paper 210 g/m², 24 in. x 100 ft/610 mm x 30,5 m C7660A HP Premium Matte Photo Paper 210 g/m², 36 in. x 100 ft/914 mm x 22,9 m (NA, EMEA, AP only) Q8834A HP Self-adhesive Gloss Polypropylene 120 g/m², 36 in. x 75 ft/914 mm x 22,9 m Q1442A HP Coatled Paper 90 g/m², (Al) 23.39 in. x 150 ft/594 mm x 45,7 m (EMEA & JP only) CG886A HP Cockle-free Heavyweight Coated Paper 170 g/m², 24 in. x 100 ft/610 mm x 30,5 m (US & EMEA only) CG887A HP Cockle-free Heavyweight Coated Paper 170 g/m², 36 in. x 100 ft/914 mm x 30,5 m (US & EMEA only) CG888A HP Cockle-free Heavyweight Coated Paper 170 g/m², 42 in. x 100 ft/1067 mm x 30,5 m (US & EMEA only) CG888A HP Cockle-free Heavyweight Coated Paper 170 g/m², 42 in. x 100 ft/1067 mm x 30,5 m (US & EMEA only) CG888A HP Cockle-free Coated Paper 100 g/m², 36 in. x 150 ft/610 mm x 45,7 m (US & EMEA only) CG889A HP Cockle-free Coated Paper 100 g/m², 36 in. x 150 ft/610 mm x 45,7 m (US & EMEA only) CG889A HP Cockle-free Coated Paper 100 g/m², 36 in. x 150 ft/610 mm x 45,7 m (US & EMEA only) CG889A HP Cockle-free Coated Paper 100 g/m², 36 in. x 150 ft/610 mm x 45,7 m (US & EMEA only) CG889A HP Recycled Bond Paper 80 g/m², 41 in. x 150 ft/610 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG890A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG891A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG894A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/10	Q1445A	HP Bright White Inkjet Paper 90 g/m², (A1) 23.39 in. x 150 ft/594 mm x 45,7 m	
C3875A	<u> </u>	now with ColorPRO Technology	
S16428			
G1427A			
(INA, EMEA, AP only) Q1421A			
(NA, EMEA, AP only) CG459A HP Premium Matte Photo Paper 210 g/m², 24 in. x 100 ft/610 mm x 30,5 m CG460A HP Premium Matte Photo Paper 210 g/m², 36 in. x 100 ft/914 mm x 30,5 m C7960A HP Reverse Print Matte Backlit Film 160 g/m², 36 in. x 75 ft/914 mm x 22,9 m (NA, EMEA, AP only) Q8834A HP Self-adhesive Gloss Polypropylene 120 g/m², 36 in. x 75 ft/914 mm x 22,9 m Q1442A HP Coated Paper 90 g/m², (A1) 23.39 in. x 150 ft/594 mm x 45,7 m (EMEA & JP only) CG886A HP Coated Paper 90 g/m², (A1) 23.39 in. x 150 ft/594 mm x 45,7 m (EMEA & JP only) CG886A HP Cockle-free Heavyweight Coated Paper 170 g/m², 24 in. x 100 ft/610 mm x 30,5 m (US & EMEA only) CG887A HP Cockle-free Heavyweight Coated Paper 170 g/m², 36 in. x 100 ft/914 mm x 30,5 m (US & EMEA only) CG888A HP Cockle-free Heavyweight Coated Paper 170 g/m², 42 in. x 100 ft/1067 mm x 30,5 m (US & EMEA only) CG883A HP Cockle-free Coated Paper 100 g/m², 24 in. x 150 ft/610 mm x 45,7 m (US & EMEA only) CG885A HP Cockle-free Coated Paper 100 g/m², 36 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) CG885A HP Cockle-free Coated Paper 100 g/m², 24 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) CG889A HP Recycled Bond Paper 80 g/m², 24 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG890A HP Recycled Bond Paper 80 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG891A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG892A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG892A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG892A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper Service and support US245E 3 year, Next business day, Onsite Support US245E 1 year, Post Warranty, Next business day, Onsite Support US23	Q1421A	(NA, EMEA, AP only)	
CG460A		(NA, EMEA, AP only)	
C7960A			
(NA, EMEA, AP only) Q8834A			
CG886A		(NA, EMEA, AP only)	
CG886A			
(US & EMEA only) CG887A			
(US & EMEA only) CG888A		(US & EMEA only)	
(US & EMEA only) (US & EMEA only) CG883A HP Cockle-free Coated Paper 100 g/m², 24 in. x 150 ft/610 mm x 45,7 m (US & EMEA only) CG884A HP Cockle-free Coated Paper 100 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only) CG885A HP Cockle-free Coated Paper 100 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) HP Recycled Bond Paper 80 g/m², 24 in. x 150 ft/610 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG890A HP Recycled Bond Paper 80 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG891A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG892A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper Service and support US251E 3 year, Next business day, Onsite Support US245E 5 year, Next business day, Onsite Support US245E 1 year, Next business day, Onsite Support US245E 1 year, Post Warranty, Next business day, Onsite Support US245E 1 year, Post Warranty, Next business day, Onsite Support US239FE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support		(US & EMEA only)	
CG884A HP Cockle-free Coated Paper 100 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only) CG885A HP Cockle-free Coated Paper 100 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) CG889A HP Recycled Bond Paper 80 g/m², 24 in. x 150 ft/610 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG890A HP Recycled Bond Paper 80 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG891A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG892A HP Recycled Bond Paper 80 g/m², (A2) 16.54 in. x 150 ft/420 mm x 45,7 m (EMEA only) made of 100% recycled base paper Service and support US251E 3 year, Next business day, Onsite Support US250E 4 year, Next business day, Onsite Support US245E 1 year, Next business day, Onsite Support US245E 1 year, Post Warranty, Next business day, Onsite Support US239PE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support US239PE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support		(US & EMEA only)	
CG885A HP Cockle-free Coated Paper 100 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) CG889A HP Recycled Bond Paper 80 g/m², 24 in. x 150 ft/610 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG890A HP Recycled Bond Paper 80 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG891A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG892A HP Recycled Bond Paper 80 g/m², (A2) 16.54 in. x 150 ft/420 mm x 45,7 m (EMEA only) made of 100% recycled base paper Service and support US251E 3 year, Next business day, Onsite Support US250E 4 year, Next business day, Onsite Support US250E 4 year, Next business day, Onsite Support US245E 1 year, Post Warranty, Next business day, Onsite Support US239PE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support			
CG889A HP Recycled Bond Paper 80 g/m², 24 in. x 150 ft/610 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG890A HP Recycled Bond Paper 80 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG891A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG892A HP Recycled Bond Paper 80 g/m², (A2) in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG892A HP Recycled Bond Paper 80 g/m², (A2) 16.54 in. x 150 ft/420 mm x 45,7 m (EMEA only) made of 100% recycled base paper Service and support US251E 3 year, Next business day, Onsite Support US249E 5 year, Next business day, Onsite Support US244E 3 year, Next business day, Onsite Support US245FE 1 year, Post Warranty, Next business day, Onsite Support US239PE 1 year, Post Warranty, 14 hour response 13 by 5 Onsite Support			
made of 100% recycled base paper CG890A HP Recycled Bond Paper 80 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG891A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG892A HP Recycled Bond Paper 80 g/m², (A2) 16.54 in. x 150 ft/420 mm x 45,7 m (EMEA only) made of 100% recycled base paper Service and support US251E 3 year, Next business day, Onsite Support US249E 5 year, Next business day, Onsite Support US250E 4 year, Next business day, Onsite Support US244E 3 year, 4 hour response 13 by 5 Onsite Support US244E 1 year, Post Warranty, Next business day, Onsite Support US239PE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support			
CG891A HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only) made of 100% recycled base paper CG892A HP Recycled Bond Paper 80 g/m², (A2) 16.54 in. x 150 ft/420 mm x 45,7 m (EMEA only) made of 100% recycled base paper Service and support US251E 3 year, Next business day, Onsite Support US249E 5 year, Next business day, Onsite Support US245E 4 year, Next business day, Onsite Support US244E 3 year, 4 hour response 13 by 5 Onsite Support US245PE 1 year, Post Warranty, Next business day, Onsite Support US239PE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support	CG890A	HP Recycled Bond Paper 80 g/m², 36 in. x 150 ft/914 mm x 45,7 m (US & EMEA only)	
CG892A HP Recycled Bond Paper 80 g/m², (A2) 16.54 in. x 150 ft/420 mm x 45,7 m (EMEA only) made of 100% recycled base paper US251E 3 year, Next business day, Onsite Support US249E 5 year, Next business day, Onsite Support US250E 4 year, Next business day, Onsite Support US244E 3 year, 4 hour response 13 by 5 Onsite Support US245PE 1 year, Post Warranty, Next business day, Onsite Support US239PE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support	CG891A	made of 100% recycled base paper HP Recycled Bond Paper 80 g/m², 42 in. x 150 ft/1067 mm x 45,7 m (US & EMEA only)	
Service and support US251E 3 year, Next business day, Onsite Support US249E 5 year, Next business day, Onsite Support US250E 4 year, Next business day, Onsite Support US244E 3 year, Next business day, Onsite Support US245E 1 year, Post Warranty, Next business day, Onsite Support US245PE 1 year, Post Warranty, Next business day, Onsite Support US239PE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support	CG892A	HP Recycled Bond Paper 80 g/m², (A2) 16.54 in. x 150 ft/420 mm x 45,7 m (EMEA only)	
US251E 3 year, Next business day, Onsite Support US249E 5 year, Next business day, Onsite Support US250E 4 year, Next business day, Onsite Support US244E 3 year, 4 hour response 13 by 5 Onsite Support US245PE 1 year, Post Warranty, Next business day, Onsite Support US239PE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support	Service and s		
US249E 5 year, Next business day, Onsite Support US250E 4 year, Next business day, Onsite Support US244E 3 year, 4 hour response 13 by 5 Onsite Support US245PE 1 year, Post Warranty, Next business day, Onsite Support US239PE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support			
US250E 4 year, Next business day, Onsite Support US244E 3 year, 4 hour response 13 by 5 Onsite Support US245PE 1 year, Post Warranty, Next business day, Onsite Support US239PE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support	US249E	5 year, Next business day, Onsite Support	
US245PE 1 year, Post Warranty, Next business day, Onsite Support US239PE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support		4 year, Next business day, Onsite Support	
US239PE 1 year, Post Warranty, 4 hour response 13 by 5 Onsite Support			

For more HP large-format printing materials and sizes please visit us online at: www.hp.com/go/designjet/supplies

- Mechanical printing time

- Mechanical printing time
 Printed on plain media with Economode on
 Printed on glossy media
 +/-0.1% of the specified vector length or +/-0.1 mm (whichever greater) at 23° C (73° F), 50-60% relative
 humidity, on A0/C printing material in Best or Normal mode with HP Matte Film
 Measured on HP Matte Film
 384 MB RAM

© Copyright 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe PostSript 3 is a trademarks of Adobe Systems Incorporated. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. AMD is a trademark of Advanced Micro Devices, Inc. Intel and Pentium are trademarks of Intel Corporation in the U.S. and other countries. Windows, Windows XP, and Windows Vista are U.S. registered trademarks of Microsoft Corporation.

