



# HP 1905 Switch Series



## Key features

- Customized operation using intuitive Web interface
- Fast Ethernet Layer 2 operation
- Access control lists for enhanced security
- Spanning Tree: STP and RSTP
- 3-year warranty

## Product overview

HP 1905 Switch Series devices are smart-managed fixed-configuration Fast Ethernet Layer 2 switches designed for small businesses looking for key features in an easy-to-administer, low-cost solution. Series models include: 24- and 48-port non-PoE switches, 8- and 24-port PoE Fast Ethernet switches. These smart-managed switches come preconfigured for fast and easy installation, yet allow network operation to be enhanced using an intuitive Web-based management interface. Advanced security and quality-of-service features create a voice-ready network. HP 1905 series switches are solidly built for business operation, and are designed for high reliability, long life, low power consumption, and low total cost of ownership. The HP 1905 switches come with a 3-year warranty, covering unit, fans, and power adapters or power supplies.

## Features and benefits

### Quality of Service (QoS)

- **Traffic prioritization (IEEE 802.1p)**  
allows real-time traffic classification mapped to four hardware queues per port

### Management

- **Simple Web management**  
easy device management even by nontechnical users enabled by intuitive Web GUI
- **Secure web GUI**  
provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **SNMPv1, v2c**  
devices can be discovered and monitored from an SNMP management station
- **Port mirroring**  
allows traffic to be mirrored on any port or a network analyzer to assist with diagnostics or detecting network attacks
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**  
automated device discovery protocol for easy mapping by network management applications

### Connectivity

- **Auto-MDIX**  
automatically adjusts for straight-through or crossover cables on all ports
- **Front-panel LEDs**  
provide an at-a-glance view of status, activity, speed, and full-duplex operation
- **Flow control**  
helps ensure reliable communications during full-duplex operation
- **Small Form-Factor Pluggable (SFP) slots**  
allow for fiber connectivity
- **Cable diagnostics**  
remotely detect cable issues using a browser-based tool

### Performance

- **Link aggregation (trunking)**  
groups together up to eight links per trunk to increase bandwidth and create redundant connections
- **IGMP snooping**  
multicast filtering improves network performance, instead of flooding traffic to all ports

### Layer 2 switching

- **VLAN support and tagging**  
supports up to 64 port-based VLANs and dynamic configuration of IEEE 802.1Q VLAN tagging, providing security between workgroups

- **Spanning Tree (STP/RSTP)**  
prevents network loop

### Security

- **Access control lists (ACLs)**  
allow network managers to define classification actions and rules for specific ingress ports
- **Secure Sockets Layer (SSL)**  
encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **IEEE 802.1X**  
utilizes an industry-standard user authentication with an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server

### Convergence

- **Auto Voice VLAN**  
recognizes IP phones and automatically assigns voice traffic to dedicated VLAN for IP phones
- **IEEE 802.3af Power over Ethernet Models**  
PoE provides up to 15.4 W per port to IEEE 802.3af-compliant PoE-powered devices such as IP phones, wireless access points, and security cameras (see product specifications for total PoE power available)

### Additional information

- **Green initiative support**  
provides support for RoHS and WEEE regulations

### Warranty and support

- **3-year warranty**  
with advance replacement and next-business-day delivery (available in most countries)
- **Electronic and telephone support**  
limited electronic and telephone support is available from HP; to reach our support centers, refer to [www.hp.com/networking/contact-support](http://www.hp.com/networking/contact-support); for details on the duration of support provided with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)
- **Software releases**  
to find software for your product, refer to [www.hp.com/networking/support](http://www.hp.com/networking/support); for details on the software releases available with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)

# HP 1905 Switch Series

## Specifications



**HP 1905-24 Switch (JD990A)**



**HP 1905-48 Switch (JD994A)**

<b>Ports</b>	24 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Media Type: Auto-MDIX; Duplex: half or full  2 RJ-45 dual-personality 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)  1 RJ-45 serial console port	48 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Media Type: Auto-MDIX; Duplex: half or full  2 RJ-45 dual-personality 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)  1 RJ-45 serial console port
<b>Physical characteristics</b>	17.4(w) x 9.4(d) x 1.7(h) in (44.2 x 23.88 x 4.32 cm) (1U height) Weight 6.8 lb (3.08 kg)	17.4(w) x 9.4(d) x 1.7(h) in (44.2 x 23.88 x 4.32 cm) (1U height) Weight 6.4 lb (2.9 kg)
<b>Memory and processor</b>	ARM 88E6218 @ 150 MHz, 8 MB SDRAM, 4 MB flash; packet buffer size: 384 KB	ARM 88E6218 @ 150 MHz, 8 MB SDRAM, 4 MB flash; packet buffer size: 384 MB
<b>Mounting</b>	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)
<b>Performance</b>	100 Mb Latency < 5 µs 1000 Mb Latency < 5 µs Throughput up to 6.6 mpps Routing/Switching capacity 8.8 Gbps	< 5 µs < 5 µs up to 10.1 mpps 13.6 Gbps
<b>Environment</b>	Operating temperature 32°F to 113°F (0°C to 45°C) Operating relative humidity 10% to 90%, noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 10% to 95%, noncondensing Acoustic Fanless	32°F to 113°F (0°C to 45°C) 10% to 90%, noncondensing -40°F to 158°F (-40°C to 70°C) 10% to 95%, noncondensing Fanless
<b>Electrical characteristics</b>	Frequency 50/60 Hz Voltage 100-240 VAC Maximum power rating 17 W Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	50/60 Hz 100-240 VAC 26 W Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
<b>Safety</b>	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A
<b>Management</b>	limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
<b>Notes</b>	The HP 1905-24 Switch (JD990A) was formerly sold as the 3Com Baseline Plus 2226 (3CBLSF26H) and may ship with this product labeling.	The HP 1905-48 Switch (JD994A) was formerly sold as the 3Com Baseline Plus 2250 (3CBLSF50H) and may ship with this product labeling.
<b>Services</b>	3-year, 4-hour onsite, 13x5 coverage for hardware (UV792E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW015E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW021E) 3-year, 24x7 SW phone support, software updates (UV795E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UV793E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW016E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW022E) 4-year, 24x7 SW phone support, software updates (UV796E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UV794E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW017E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW023E) 5-year, 24x7 SW phone support, software updates (UV797E) 3 Yr 6 hr Call-to-Repair Onsite (UW018E)	3-year, 4-hour onsite, 13x5 coverage for hardware (UV792E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW015E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW021E) 3-year, 24x7 SW phone support, software updates (UV795E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UV793E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW016E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW022E) 4-year, 24x7 SW phone support, software updates (UV796E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UV794E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW017E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW023E) 5-year, 24x7 SW phone support, software updates (UV797E) 3 Yr 6 hr Call-to-Repair Onsite (UW018E)

## HP 1905 Switch Series

### Specifications (continued)

	HP 1905-24 Switch (JD990A)	HP 1905-48 Switch (JD994A)
	<p>4 Yr 6 hr Call-to-Repair Onsite (UW019E)            5 Yr 6 hr Call-to-Repair Onsite (UW020E)            1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E)            1-year, 24x7 software phone support, software updates (HR685E)            Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>4 Yr 6 hr Call-to-Repair Onsite (UW019E)            5 Yr 6 hr Call-to-Repair Onsite (UW020E)            1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E)            1-year, 24x7 software phone support, software updates (HR685E)            Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
<b>Standards and protocols</b> (applies to all products in series)	<p><b>Device management</b> RFC 2819 RMON</p> <p><b>General protocols</b>            IEEE 802.1w Rapid Reconfiguration of Spanning Tree            IEEE 802.3ab 1000BASE-T            IEEE 802.3ac (VLAN Tagging Extension)            IEEE 802.3ad Link Aggregation Control Protocol (LACP)            IEEE 802.3i 10BASE-T            IEEE 802.3u 100BASE-X            IEEE 802.3x Flow Control            IEEE 802.3z 1000BASE-X</p> <p><b>MIBs</b>            RFC 1213 MIB II            RFC 1493 Bridge MIB            RFC 2021 RMONv2 MIB</p>	<p><b>Network management</b>            IEEE 802.1AB Link Layer Discovery Protocol (LLDP)            IEEE 802.1D (STP)            RFC 1215 SNMP Generic traps</p> <p><b>QoS/CoS</b>            IEEE 802.1P (CoS)</p> <p><b>Security</b>            IEEE 802.1X Port Based Network Access Control</p> <p>RFC 2233 Interface MIB            RFC 2233 Interfaces MIB            RFC 2571 SNMP Framework MIB            RFC 2572 SNMP-MPD MIB            RFC 2573 SNMP-Notification MIB            RFC 2573 SNMP-Target MIB            RFC 2613 SMON MIB            RFC 2618 RADIUS Client MIB            RFC 2620 RADIUS Accounting MIB            RFC 2665 Ethernet-Like-MIB            RFC 2667 IP Tunnel MIB            RFC 2668 802.3 MAU MIB            RFC 2674 802.1p and IEEE 802.1Q Bridge MIB            RFC 2737 Entity MIB (Version 2)            RFC 3414 SNMP-User based-SM MIB            RFC 3415 SNMP-View based-ACM MIB            RFC 3418 MIB for SNMPv3</p>

## HP 1905 Switch Series

### Specifications (continued)



HP 1905-24-PoE Switch (JD992A)



HP 1905-8-PoE Switch (JD877A)

	HP 1905-24-PoE Switch (JD992A)	HP 1905-8-PoE Switch (JD877A)
<b>Ports</b>	<p>24 RJ-45 autosensing 10/100 PoE ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3af PoE); Media Type: Auto-MDIX; Duplex: half or full</p> <p>2 RJ-45 dual-personality 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)</p> <p>1 RJ-45 serial console port</p>	<p>8 RJ-45 autosensing 10/100 PoE ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3af PoE); Media Type: Auto-MDIX; Duplex: half or full</p> <p>1 RJ-45 dual-personality 10/100/1000 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)</p> <p>1 RJ-45 serial console port</p>
<b>Physical characteristics</b>	<p>17.4(w) x 9.4(d) x 1.7(h) in (44.2 x 23.88 x 4.32 cm) (1U height)</p> <p>Weight 7.1 lb (3.22 kg)</p>	<p>13.0(w) x 8.0(d) x 1.7(h) in (33.02 x 20.32 x 4.32 cm) (1U height)</p> <p>4.5 lb (2.04 kg)</p>
<b>Memory and processor</b>	<p>Processor ARM 88E6218 @ 150 MHz, 8 MB SDRAM, 4 MB flash; packet buffer size: 384 MB</p>	<p>BRCM 53202 @ 133 MHz, 32 MB SDRAM, 8 MB flash; packet buffer size: 1 MB</p>
<b>Mounting</b>	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)
<b>Performance</b>	<p>100 Mb Latency &lt; 5 μs</p> <p>1000 Mb Latency &lt; 5 μs</p> <p>Throughput up to 6.6 mpps</p> <p>Routing/Switching capacity 8.8 Gbps</p>	<p>&lt; 5 μs</p> <p>&lt; 5 μs</p> <p>up to 2.7 mpps</p> <p>3.6 Gbps</p>
<b>Environment</b>	<p>Operating temperature 32°F to 113°F (0°C to 45°C)</p> <p>Operating relative humidity 10% to 90%, noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 10% to 95%, noncondensing</p> <p>Acoustic</p>	<p>32°F to 113°F (0°C to 45°C)</p> <p>10% to 90%, noncondensing</p> <p>-40°F to 158°F (-40°C to 70°C)</p> <p>10% to 95%, noncondensing</p> <p>Fanless</p>
<b>Electrical characteristics</b>	<p>Frequency 50/60 Hz</p> <p>Voltage 100-240 VAC</p> <p>Maximum power rating 205 W</p> <p>PoE power 154 W</p> <p>Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).</p>	<p>50/60 Hz</p> <p>100-240 VAC</p> <p>88 W</p> <p>62 W</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).</p>
<b>Safety</b>	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03	UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03
<b>Emissions</b>	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A
<b>Management</b>	limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB	limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB
<b>Notes</b>	The HP 1905-24-PoE Switch (JD992A) was formerly sold as the 3Com Baseline Plus 2426 PWR (3CBLSF26PWRH) and may ship with this product labeling.	The HP 1905-8-PoE Switch (JD877A) was formerly sold as the 3Com OfficeConnect Managed Fast Ethernet PoE Switch (3CRDSF9PWR) and may ship with this product labeling.
<b>Services</b>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV792E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW015E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW021E)</p> <p>3-year, 24x7 SW phone support, software updates (UV795E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV793E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW016E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW022E)</p> <p>4-year, 24x7 SW phone support, software updates (UV796E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UV794E)</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW485E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW488E)</p> <p>3-year, 24x7 SW phone support, software updates (UV789E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR684E)</p> <p>Installation with minimum configuration, system-based pricing (UW451E)</p> <p>Installation with minimum configuration, system-based pricing (UY901E)</p> <p>Installation with HP-provided configuration, system-based pricing (UY902E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV787E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW486E)</p>

## HP 1905 Switch Series

### Specifications (continued)

HP 1905-24-PoE Switch (JD992A)	HP 1905-8-PoE Switch (JD877A)
5-year, 4-hour onsite, 24x7 coverage for hardware (UW017E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW023E) 5-year, 24x7 SW phone support, software updates (UV797E) 3 Yr 6 hr Call-to-Repair Onsite (UW018E) 4 Yr 6 hr Call-to-Repair Onsite (UW019E) 5 Yr 6 hr Call-to-Repair Onsite (UW020E) 1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E) 1-year, 24x7 software phone support, software updates (HR685E) Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW489E) 4-year, 24x7 SW phone support, software updates (UV790E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UV788E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW487E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW490E) 5-year, 24x7 SW phone support, software updates (UV791E) 3 Yr 6 hr Call-to-Repair Onsite (UW491E) 4 Yr 6 hr Call-to-Repair Onsite (UW492E) 5 Yr 6 hr Call-to-Repair Onsite (UW493E)  1-year, 6 hour Call-To-Repair Onsite for hardware (HR686E) 1-year, 24x7 software phone support, software updates (HR685E) Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

<b>Standards and protocols</b> (applies to all products in series)	<b>Device management</b> RFC 2819 RMON  <b>General protocols</b> IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.3ab 1000BASE-T IEEE 802.3ac (VLAN Tagging Extension) IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-X IEEE 802.3x Flow Control IEEE 802.3z 1000BASE-X  <b>MIBs</b> RFC 1213 MIB II RFC 1493 Bridge MIB RFC 2021 RMONv2 MIB	RFC 2233 Interface MIB RFC 2233 Interfaces MIB RFC 2571 SNMP Framework MIB RFC 2572 SNMP-MPD MIB RFC 2573 SNMP-Notification MIB RFC 2573 SNMP-Target MIB RFC 2613 SMON MIB RFC 2618 RADIUS Client MIB RFC 2620 RADIUS Accounting MIB RFC 2665 Ethernet-Like-MIB RFC 2667 IP Tunnel MIB RFC 2668 802.3 MAU MIB RFC 2674 802.1p and IEEE 802.1Q Bridge MIB RFC 2737 Entity MIB (Version 2) RFC 3414 SNMP-User based-SM MIB RFC 3415 SNMP-View based-ACM MIB RFC 3418 MIB for SNMPv3	<b>Network management</b> IEEE 802.1AB Link Layer Discovery Protocol (LLDP) IEEE 802.1D (STP) RFC 1215 SNMP Generic traps  <b>QoS/CoS</b> IEEE 802.1P (CoS)  <b>Security</b> IEEE 802.1X Port Based Network Access Control
---	---	---	---

## HP 1905 Switch Series accessories

### Transceivers

HP X124 1G SFP LC SX Transceiver (JD493A)  
HP X120 1G SFP LC LX Transceiver (JD119B)  
HP X121 1G SFP LC SX Transceiver (J4858C)  
HP X121 1G SFP LC LX Transceiver (J4859C)  
HP X124 1G SFP LC LX Transceiver (JD494A)

### Cables

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)  
HP 1 m Multimode OM3 LC/LC Optical Cable (AJ834A)  
HP 2 m Multimode OM3 LC/LC Optical Cable (AJ835A)  
HP 5 m Multimode OM3 LC/LC Optical Cable (AJ836A)  
HP 15 m Multimode OM3 LC/LC Optical Cable (AJ837A)  
HP 30 m Multimode OM3 LC/LC Optical Cable (AJ838A)  
HP 50 m Multimode OM3 LC/LC Optical Cable (AJ839A)

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A)  
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable (QK733A)  
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable (QK734A)  
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable (QK735A)  
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable (QK736A)  
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable (QK737A)

SOLO NETWORK

---

**To learn more, visit [hp.com/networking](http://hp.com/networking)**

© Copyright 2010, 2011, 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

4AA1-7792ENW, Created June 2010; Updated May 2013, Rev. 4

