40<mark>62-6971 (21) 4062-6971 (31) 4062-6971 (41) 4062</mark>-6971 (48) 4062-6971 (51) 4062-6971 (61) 4062-6971 atchGuard

# WatchGuard<sup>®</sup> XTM 3 Series

### **RECOMMENDED FOR SMALL TO MIDSIZED BUSINESSES**

### **BEST-OF-BREED SECURITY**

- Application-layer content inspection recognizes & blocks threats that stateful packet firewalls cannot detect.
- Powerful subscription-based security services boost protection in critical attack areas for multiple layers of defense. By partnering with leading technology providers, WatchGuard is able to integrate best-of-breed security components into one UTM platform for stronger security at big cost savings.
  - APT Blocker is a cloud-based service that uses a combination of sandboxing and full system emulation to detect and block highly sophisticated Advanced Persistent Threats (APTs).
  - Application Control keeps unproductive, inappropriate, and dangerous applications off-limits.
  - Intrusion Prevention Service (IPS) delivers in-line protection from malicious exploits, including buffer overflows, SQL injections, and cross-site scripting attacks.
  - WebBlocker controls access to sites that host objectionable material or pose network security risks.
  - Gateway AntiVirus (GAV) scans traffic on all major protocols to stop threats.
- spamBlocker delivers continuous protection from unwanted and dangerous email.
- Reputation Enabled Defense ensures faster, safer web surfing with cloud-based reputation lookup.
- Data Loss Prevention (DLP) automatically inspects data in motion for corporate policy violations.
- Advanced networking features, such as link aggregation, allow you to add security without needing to change existing network infrastructure.
- Multiple VPN choices (IPSec, SSL, L2TP) for secure remote access include support for Android and Apple iOS devices.

### **EASY TO MANAGE**

- Interactive, real-time monitoring and reporting at no additional charge give an unprecedented view into network security activity so you can take immediate preventive or corrective actions.
- WatchGuard Dimension<sup>™</sup>, a public and private cloud-ready visibility solution, instantly turns raw data into security intelligence.
- RapidDeploy<sup>™</sup> enables quick, secure configuration at remote locations without technical staff.
- Intuitive management console centrally manages all security functions.
- WAN and VPN failover provide redundancy for increased reliability.
- Extend best-in-class UTM security to the WLAN by adding WatchGuard's Wireless Access Points.
- Drag-and-drop Branch Office VPN setup three clicks and your remote office is connected.

### **HIGHEST UTM PERFORMANCE IN THE INDUSTRY**

- Firewall throughput of up to 1.4 Gbps and UTM throughput of up to 298 Mbps to keep traffic moving.
- No need to compromise protection for strong performance or vice versa. Multi-layered, interlocking security protects the network while throughput remains high.
- Gigabit Ethernet ports support high-speed LAN backbone infrastructures & gigabit WAN connections.

### WIRED OR WIRELESS – YOUR CHOICE

- The XTM 33-W is a wireless model that includes optional dual-band 802.11/n technology for much more responsive wireless network connection and expanded range. 2.4 GHz or less crowded 5 GHz band.
- Multiple security zones give administrators precise control over Internet access privileges for different user groups.
- Wireless guest services segment the Internet for customers/guests.

### WHY BUY AN ALL-IN-ONE SOLUTION FROM WATCHGUARD?

Datasheet

An all-in-one XTM network security solution integrates complete protection while slashing the time and cost associated with managing multiple single-point security products. All security capabilities work together for a holistic, comprehensive approach to network protection. Your IT staff has more time to focus on other areas of network administration, and your business saves money on support and hardware costs.

### "WatchGuard makes a great firewall and security appliance, and backs it up with tremendous and personal support."

Chet Cromer President C2IT Consulting, Inc.

XTM 3 Series	XTM 33	XTM 33-W	XTM 330
THROUGHPUT			
Firewall throughput**	850 Mbps	850 Mbps	1.4 Gbps
VPN throughput**	100 Mbps	100 Mbps	240 Mbps
AV throughput**	175 Mbps	175 Mbps	340 Mbps
IPS throughput**	328 Mbps	328 Mbps	640 Mbps
UTM throughput**	146 Mbps	146 Mbps	298 Mbps
Interfaces 10/100/1000 <sup>+</sup>	5 copper	5 copper	7 copper
I/O interfaces	1 SRL/1 USB	1 SRL/1 USB	1 SRL/2 USB
Concurrent connections (bi-directional)	40,000	40,000	40,000
New connections per second	3,800	3,800	5,500
VLANs	75	75	75
WSM licenses (incl)	4	4	4
Authenticated users limit	500	500	500
Wireless	-	802.11a/b/g/n	-
VPN TUNNELS			
Branch Office VPN	50	50	50
Mobile VPN IPSec (incl/max)	5/55	5/55	5/55
Mobile VPN SSL/L2TP	55	55	55

# SECURITY FEATURES Firewall Stateful packet inspection, deep packet inspection, proxy firewall

mewan	Stateral packet inspection, accp packet inspection, proxy incluai	
Application proxies	HTTP, HTTPS, SMTP, FTP, DNS, TCP, POP3	
Threat protection	DoS attacks, fragmented & malformed packets, blended threats & more	
VoIP	H.323, SIP, call setup and session security	
Filtering options	Browser Safe Search, YouTube for Schools	
Security subscriptions	Application Control, IPS, WebBlocker, GAV, DLP, spamBlocker, Reputation Enabled Defense, APT Blocker	
<b>VPN &amp; AUTHENTICATION</b>		
Encryption	DES, 3DES, AES 128-, 192-, 256-bit	
IPSec	SHA-1, SHA-2, MD5, IKE pre-shared key, 3rd party cert	
Single sign-on	Supports Windows, Mac OS X, mobile operating systems	
Authentication	RADIUS, LDAP, Windows Active Directory, VASCO, RSA SecurID, internal database	
MANAGEMENT		
Logging and notifications	WatchGuard, Syslog, SNMP v2/v3	
User interfaces	Centralized console (WSM), Web UI, scriptable CLI	
Reporting	WatchGuard Dimension includes 70 pre-defined reports, executive summary and visibility tools	
CERTIFICATIONS		
Security	ICSA Firewall, ICSA IPSec VPN, CC EAL4+, FIPS 140-2	
Safety	NRTL/C, CB	
Network	IPv6 Ready Gold (routing)	
Hazardous substance control	WEEE, RoHS, REACH	
NETWORKING		
Routing	Static, Dynamic (BGP4, OSPF, RIP v1/v2), Policy-based VPN	
High Availability	Active/passive, active/active with load balancing	
QoS	8 priority queues, DiffServ, modified strict queuing	
IP address assignment	Static, DHCP (server, client, relay), PPPoE, DynDNS	



### PHYSICAL AND POWER SPECIFICATIONS

Product Dimensions			
33 Wired	6.1" x 7.5" x 1.25" (15.5 x 19.0 x 3.2 cm)		
33 Wireless (antennae up)	7.75″ x 10.75″ x 5″ (19.7 x 27.3 x 12.7 cm)		
330	11.25" x 17" x 1.75" (28.6 x 43.2 x 4.5 cm)		
Shipping Dimensions			
33 Wired or Wireless	10.75" x 13.25" x 3.4" (27.3 x 33.7 x 8.6 cm)		
330	18″ x 21″ x 5.25″ (45.7 x 53.3 x 13.3 cm)		
Shipping Weight			
33 Wired / Wireless	3.2 lbs (1.45 Kg) / 3.6 lbs (1.6 Kg)		
330	16.1 lbs (7.3 Kg)		
Power Consumption			
33 Wired	U.S. 23.33 Watts (80 BTU/hr)		
33 Wireless	U.S. 24.0 Watts (82 BTU/hr)		
330	U.S. 50 Watts (171 BTU/hr)		
AC Power	100-240 VAC Autosensing		
Rack Mountable	1U rack mount kit included with XTM 330 only		
ENVIRONMENT	OPERATING	STORAGE	
Temperature			
33 Wired or Wireless	32° F to 104° F 0° C to 40° C	-40° F to 158° F -40° C to 70° C	
330	32° F to 104° F 0° C to 40° C	-40° F to 158° F -40° C to 70° C	
Relative Humidity	10% to 85% non-condensing	10% to 95% non-condensing	
Altitude	0 to 9,843 ft at 95° F (3,000 m at 35° C)	0 to 15,000 ft at 95° F (4,570 m at 35° C)	
MTBF			
33 Wired or Wireless	129,955 hours @ 104° F(40° C)		
330	51,644 hours @ 77° F (25° C)		

### **STRONG SECURITY AT EVERY LAYER**

WatchGuard uses a best-of-breed strategy to create the most reliable security solutions on the market. By partnering with industry-leading technology vendors, WatchGuard delivers an all-star family of UTM network security products.

SOPHOS







X lastline



## EXPERT GUIDANCE AND SUPPORT

An initial subscription to LiveSecurity<sup>®</sup> Service is included with every XTM 3 Series appliance. LiveSecurity provides hardware warranty with advance hardware replacement, technical support, and software updates.

### **MULTIPLE PURCHASE OPTIONS**

The flexibility of WatchGuard's integrated UTM platform makes it easy to have exactly the security components your business network requires. Talk to your authorized WatchGuard reseller about very affordable bundled subscriptions for the XTM 3 Series.

\*\*Throughput rates are determined using multiple flows through multiple ports and will vary depending on environment and configuration. Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network.

Static, dynamic, 1:1, IPSec traversal, policy-based

Port Independence, Multi-WAN failover and load balancing<sup>†</sup>,

<sup>†</sup>Server load balancing is not available on XTM 3 Series models.

NAT

Link aggregation Other features

### U.S. SALES 1.800.734.9905 INTERNATIONAL SALES +1.206.613.0895

Static, active/backup

transparent/drop-in mode

www.watchguard.com

No express or implied warranties are provided for herein. All specifications are subject to change and expected future products, features or functionality will be provided on an if and when available basis. © 2014 WatchGuard Technologies, Inc. All rights reserved. WatchGuard, the WatchGuard logo, Fireware, and LiveSecurity are registered trademarks of WatchGuard Technologies, Inc. in the United States and/or other countries. All other tradenames are the property of their respective owners. Part No. WGCE66745\_100114